



GRINDER CONTROL PANEL LAYOUT

BILL OF MATERIALS	
ITEM	EQUIPMENT DESCRIPTION
1	LAMACOID, WHITE W/BLACK 20mm LETTERS
2	PILOT LIGHT - WHITE, 30mm
3	PILOT LIGHT - AMBER, 30mm
4	PILOT LIGHT - RED, 30mm
5	PUSH BUTTON, BLACK, FLUSH HEAD, 30mm
6	3 POSITION SELECTOR SWITCH, KNOB LEVER, BLACK, MAINTAINED, 30mm
7	3 POSITION SELECTOR SWITCH, SPRING RETURN FROM BOTH, BLACK, 30MM
8	PUSH BUTTON, RED, MUSHROOM HEAD, TWIST RELEASE
9	LEGEND PLATE, E-STOP, ROUND, 60mm
10	ENGRAVED LEGEND PLATE, ALUMINUM W/BLACK LETTERS (8mm)
11	MAIN DISCONNECT

NOTES:

1. SHORT CIRCUIT CURRENT (SCCR) FOR THE CONTROLLER IS 18kA @ 600V.
2. A JUMPER IS PRE-INSTALLED; INSTALLATION CONTRACTOR TO REMOVE AND CONNECT TO GRINDER MOTOR OVER TEMPERATURE.



PUBLIC WORKS  
STANDARD DRAWING

REV. DATE: JULY 2021

APPROVED BY  
MM

DRAWN BY  
ERAMOSA

INLET GRINDER CONTROL  
PANEL LAYOUT

STD. DWG. NUMBER  
SPS-211

SCALE  
Not to Scale